



LIGHT DISTRIBUTION



CROSS-SECTION



OPTICAL SYSTEM

1. VERSATILE LIGHT ENGINE

Multiple Lumen Intensities Provide the Correct Level of Illumination Within Each Space

2. EVENLY ILLUMINATED LOWER LENS

High Efficiency Diffuser Designed to Minimize Glare and Provide Uniform Light Distribution

HOUSING

3. HIDDEN CONNECT

Recessed Connection Point Between Cable and Fixture Eliminates the Visibility of Hardware

4. SURE-FIT ALIGNMENT

6-Point Alignment System Adjoining Each Luminaire Section to Ensure Straighter Rows While Minimizing the Appearance of Seams

ELECTRICAL

5. EFFICACY

Luminaire Efficacy of 83.4 Lumens per Watt Helps Achieve Best in Class Power Density Performance

DIMMING

6. 0-10 VOLT DIMMING STANDARD

See Options Below for Additional Dimming Options

| SERIES | LENGTH ¹ | OUTPUT ² | RATIO ³ U/D | VOLTAGE | CCT | MOUNTING | COLOR | DIMMING |
|-------------|--|---|------------------------|----------------------------------|---|--|---|---|
| SQ 2 | | | 01 | | | | | |
| | XXX FT 2' INCREMENTS EX: 4' = 004 | H2 1800 LM/FT H1 1500 LM/FT H 1200 LM/FT M 900 LM/FT L 600 LM/FT | 01 0/100 | 12 120V 27 277V | 30 3000K 35 3500K 40 4000K | AIRCRAFT CABLE 36" CABLE STANDARD T1 1" T GRID T9 9/16" T GRID SC SCREW SLOT GRID HC HARD CEILING | RIGID STEM ⁶ 24" STEM STANDARD RS RIGID STEM RSS RIGID SWIVEL STEM G CHARCOAL GREY | W WHITE S SILVER ND NO DIMMING |

OPTIONS

| | | | |
|--|--|---------------------------------------|---------------------------------------|
| EM ⁷ EMERGENCY BATTERY PACK | DS DAYLIGHT SENSOR | CB48 48" CABLES | RSS36 36" RIGID SWIVEL STEM |
| EC EMERGENCY CIRCUIT | OS OCCUPANCY SENSOR | CB72 72" CABLES | RSS48 48" RIGID SWIVEL STEM |
| NC NIGHT LIGHT CIRCUIT | DOS DUAL DAYLIGHT & OCCUPANCY SENSOR | CB120 ⁵ 120" CABLES | RSS72 72" RIGID SWIVEL STEM |
| GTD GENERATOR TRANS. DEVICE | FS FUSING | RS36 36" RIGID STEM | |
| | C90 ⁴ 90 CRI | RS48 48" RIGID STEM | |
| | | RS72 72" RIGID STEM | |

¹Nominal length
²Nominal lumens per foot
³Ratio defined as percentage of light illuminated upwards versus percentage of light illuminated downwards
⁴80 CRI standard
⁵For cable lengths longer than 120" please consult factory
⁶All non-aircraft cable mounting requires adder-fee
⁷Not available in H1 & H2 outputs



MECHANICAL

Housing Construction:

Extruded Aluminum 6063-T5 alloy outer housing with die-formed steel internal components for strength, alignment and mounting attachment.

Alignment/Assembly:

The Sure-Fit alignment system employs a six-point alignment and attachment method, designed to create straighter rows and minimize seams between sections (field assembled). Two alignment tabs ensure the outer extruded aluminum rails are aligned, while four draw-screws secure housing-to-housing attachment.

Lengths:

The SQ2 is available in individual 2-foot (24"), 4-foot (48"), 6-foot (72"), 8-foot (96") and 10-foot (120") lengths. Longer fixture rows are available and will be configured per Lumato factory specifications; typical rows are configured with 8-foot fixtures. Each end cap adds .0625" to the length of each fixture run. End Caps: End caps are fabricated from 16-gauge steel and finished to match housing. End caps are installed at factory with no exposed fasteners to ensure minimal visible seam.

Mounting Method/Hardware:

The Hidden-Connect design recesses all attachment hardware (hanging cable and power cord) below the top plane of the housing to enable a sleek, clean finished look. Standard hanging hardware includes 1/16" diameter, galvanized steel aircraft cable with adjustable and lockable nickel-plated cable grippers and a white 18/5 S.O. power cord. The standard hardware includes a 48" power cord and 42" aircraft cables to accommodate a 36" mounting distance from the ceiling. Longer hanging cables and power cords available as an option. Ceiling canopy provided. All Lumato suspension hardware is tested and listed to UL1598 requirements for loading/fixture support.

Exterior Finish:

The SQ2 is available in White, Silver, or Charcoal Grey polyester powder coat finish to ensure durability. Luminaires are available in any RAL color as an option.

OPERATION

Light Engine:

The SQ2 is available in 3000K, 3500K & 4000K CCT all within a 2.5-Step MacAdam Ellipse and has a standard CRI of 80+ with a 90+ CRI option available.

Optics:

The edge lit PMMA acrylic light guide ensures high efficiency light output, in a minimal form factor. A secondary acrylic diffuser is added to create a clean, evenly illuminated lower surface with minimal glare.

Electrical:

Class 2 driver, 100 watt maximum output, 120-277VAC input. Power factor >0.9. THD <15%. Integral Surge Protection to 2KV.

Dimming:

The SQ2 comes standard with 0-10V dimming. The 0-10V control allows dimming down to 10% (Dimming down to 1% is also an option; please consult factory). DALI dimming is available as an option and allows for dimming down to 1%.

Optional Controls:

The SQ2 is available with optional integrated daylight and occupancy sensors. Sensors extend the length of the luminaire and are located at the end of a row, near the power cord. Contact factory for custom locations.

GENERAL

Warranty:

Five (5) year limited warranty from date of shipment, covers LED's, driver, and luminaire. Optional accessories are covered by their individual Manufacturers warranties.

Lumen Maintenance:

Rated for 85% initial lumen output (L85) at 50,000 Hours of operation, operated at 25C ambient temperature; per TM-21 Guidelines published by the Illuminating Engineering Society (IES).

Certification

All luminaires are UL and cUL Listed, approved for Dry/Damp locations

Angeled Connectors

Angled luminaire connectors are available in "L", "T", and "X" configurations to achieve a variety of shapes. Consult factory for drawings and specifications


Made in the USA

All Lumato Luminaires and Components (with the exception of our LED boards and drivers) are proudly manufactured and assembled in the USA

PHOTOMETRICS

SQ2-4-H2-01-12-30-XX-X

Total Lumens: 6900
Ratio: 0% Up and 100% Down
Wattage: 82.7
Efficacy: 83.4 (Lumens Per Watt)
Report Number: ITL86879
Fixture Length: Four Feet



Zonal Lumen Summary

| Zone | Lumens | % Fixt |
|----------|--------|--------|
| 0 - 30 | 1670 | 24.2 |
| 0 - 40 | 2863 | 41.5 |
| 0 - 60 | 5405 | 78.3 |
| 0 - 90 | 6900 | 100.0 |
| 90 - 180 | 0 | 0.0 |
| 0 - 180 | 6900 | 100.0 |

ENERGY CONSUMPTION

Watts Per Linear Foot

| | H2:1800 | H1:1500 | H:1200 | M:900 | L:600 |
|-------|---------|---------|--------|-------|-------|
| 0/100 | 20.68 | 17.16 | 13.72 | 10.30 | 6.80 |